


V393
.R46

LIBRARIES



3 9080 02754 4458



DEPARTMENT OF THE NAVY
DAVID TAYLOR MODEL BASIN




HYDROMECHANICS

CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26

by

AERODYNAMICS

John T. Cummings




STRUCTURAL
MECHANICS

STRUCTURAL MECHANICS LABORATORY
RESEARCH AND DEVELOPMENT REPORT

APPLIED
MATHEMATICS

March 1963

Report 1704



CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26

by

John T. Cummings

March 1963

Report 1704
S-F013 11 01

TABLE OF CONTENTS

	Page
ABSTRACT	1
INTRODUCTION	1
PARAMETERS USED IN CALCULATIONS	1
RESULTS OF CALCULATIONS	2
ACKNOWLEDGMENT	3
REFERENCES	14

LIST OF TABLES

	Page
Table 1 - Principal Dimensions of AGS 26	3
Table 2 - Mass and Stiffness Data for Computing Vertical Flexural Vibration	4
Table 3 - Natural Frequencies of Vertical Flexural Vibration ..	5
Table 4 - Calculation of Two-Noded Vertical Natural Frequency of AGS 26 by Burrill Empirical Formula	5

LIST OF FIGURES

	Page
Figure 1 - Outboard Profile of AGS 26 Showing Station Locations	6
Figure 2 - Moments of Inertia Distribution for AGS 26 with respect to Horizontal Axis through Centroids of Sections	7
Figure 3 - Calculated Normal Mode Profiles and Natural Frequencies of Vertical Vibration	8-9
Figure 4 - Moment Distribution for Vertical Flexural Vibration, Assuming Unit Deflection at Stern	10-11
Figure 5 - Response to a 1-Ton Single Amplitude Sinusoidal Forcing Function at Selected Hull Stations, Damping Constant = $0.01\mu\omega$	12
Figure 6 - Response to a 1-Ton Single Amplitude Sinusoidal Forcing Function at Selected Hull Stations, Damping Constant = $0.03\mu\omega$	13

ABSTRACT

The normal mode shapes, natural frequencies, and bending moment distribution of vertical flexural vibration of the hull were calculated for the AGS 26, a Surveying Ship. Parameters used in calculations with a digital computer are tabulated. The two-noded vertical natural frequency obtained with the computer agrees closely with that calculated using the Burrill empirical formula.

INTRODUCTION

The AGS 26 is a Surveying Ship, the first ship of its class. The principal dimensions are given in Table 1. The Bureau of Ships requested that the David Taylor Model Basin calculate the normal hull modes and natural frequencies.¹ The first six vertical flexural modes and natural frequencies are presented here.

PARAMETERS USED IN CALCULATIONS

The parameters for the calculation of the normal modes and natural frequencies were computed by M. Rosenblatt and Son, Inc., according to the procedures developed at the Model Basin.²

The vertical flexural response was calculated by assuming the hull to behave like a free-free continuous nonuniform beam. The mathematical formulation and solution of these equations are discussed in detail in References 3 and 4.

Since the parameters in these equations cannot be easily expressed as continuous functions of position along the ship, a numerical method of solution using finite difference equations was used. The hull was divided into twenty equally spaced sections of 14.0 ft. each. The result obtained depends on the values for ship mass, virtual mass, bending stiffness (EI), and shear rigidity (KAG) at each station.

Figure 1 is an outboard profile of AGS 26 showing the station locations. Figure 2 is a plot of the moments of inertia distribution with respect to the horizontal axis through the centroids of the sections.

¹References are listed on page 14.

Table 2 presents the mass and stiffness data used.

RESULTS OF CALCULATIONS

Figure 3 shows the calculated normal mode profiles and natural frequencies of vertical vibration for the two-through seven-noded vibrations. The amplitudes illustrated are relative to a unit displacement input at the stern of the ship, Station 0. The moment distribution relative to this unit displacement (1 ft) is plotted in Figure 4 for each mode shape.

Figures 5 and 6 show the calculated response curves for Hull Stations 2, 10, and 20. A lumped damping constant as developed in Reference 5 and used in References 6 and 7 was applied; it is governed by the following equation:

$$\frac{c}{\mu\omega} = \frac{\frac{C}{\Delta x}}{\frac{m}{\Delta x} \omega}$$

where C is the lumped damping constant of section Δx in ton-sec/ft,
c is the distributed damping constant in ton-sec/ft,²
m is the lumped mass of section Δx in ton-sec²/ft,
 μ is the mass per unit length in ton-sec²/ft,²
 Δx is the selected span length in ft, and
 ω is the forcing frequency on the beam in radians/sec.

Values of $c = 0.01 \mu\omega$ and $c = 0.03 \mu\omega$ were used because they are considered appropriate values for calculations involving vertical vibration.

Response curves are plotted for the forcing function applied at Station 1. This forcing function was a unit sinusoidal force (1-ton single amplitude) constant over the frequency range of 1 to 50 cps.

Table 3 summarizes the natural frequencies of vertical flexural vibration. Table 4 shows the computation of the two-noded natural frequency using the empirical Burrill method.^{5,8} The dimensions used in these calculations were obtained from References 9 and 10.

ACKNOWLEDGMENT

The programming of the computed parameters for the 7090 digital computer was carried out by Dr. E. H. Cuthill and Mrs. N. G. Millett of the Applied Mathematics Laboratory of the Taylor Model Basin.

TABLE 1
Principal Dimensions of AGS 26

Ship Length between Perpendiculars, ft	283
Beam, ft	48
Draft, ft	15
Height to Main Deck, ft	23.5
Displacement, tons	2595

TABLE 2

Mass and Stiffness Data for Computing Vertical Flexural Vibration

Station	ship mass $\mu \Delta x$ ton-sec ² /ft	$\frac{\Delta x}{KAG} \times 10^5$ [*] 1/ton-ft	$\frac{\Delta x}{EI} \times 10^8$ ft./ton	
0			0	$\Delta x = 14.00$ ft. $E = 13.4 \times 10^3$ ton/in. ² $G = 5.36 \times 10^3$ ton/in. ²
1/2	1.92	22.727		
1		3.506	15.328	
1 1/2	2.51	2.693		
2		2.728	9.652	
2 1/2	4.56	2.764		
3		2.735	9.223	
3 1/2	6.07	2.612		
4		2.407	9.184	
4 1/2	7.96	2.073		
5		1.741	8.957	<p>*Note: Moments of inertia for full stations were calculated by M. Rosenblatt & Son, Inc. Those for half stations were taken from the moment curve prepared by Rosenblatt. The Applied Mathematics Laboratory, DTMB, used the full station data in its calculations.</p>
5 1/2	11.19	1.505		
6		1.329	8.724	
6 1/2	10.75	1.187		
7		1.080	8.552	
7 1/2	12.59	0.991		
8		0.916	8.452	
8 1/2	13.35	0.854		
9		0.811	8.502	
9 1/2	13.15	0.783		
10		0.800	8.436	
10 1/2	13.84	0.757		
11		0.704	7.429	
11 1/2	11.85	0.656		
12		0.645	7.304	
12 1/2	11.41	0.653		
13		0.665	7.429	
13 1/2	9.99	0.679		
14		0.700	7.207	
14 1/2	8.61	0.724		
15		0.754	6.636	
15 1/2	6.99	0.794		
16		0.846	6.046	
16 1/2	5.49	0.913		
17		1.000	5.947	
17 1/2	3.46	1.102		
18		1.211	5.915	
18 1/2	2.32	1.296		
19		1.811	6.327	
19 1/2	1.55	5.224		
20			0	

TABLE 3

Natural Frequencies of Vertical Flexural Vibration

Mode	Number of Nodes	Vertical Flexural Frequency cps
1st	2	2.98
2nd	3	5.93
3rd	4	9.05
4th	5	12.30
5th	6	15.59
6th	7	18.31

TABLE 4

Calculation of Two-Noded Vertical Natural Frequency of AGS 26 by Burrill Empirical Formula

1. Beam = B = 48 ft Displacement = Δ = 2595 tons
 Draft = d = 15 ft Length between perpendiculars = L = 283 ft
 Height to Main Deck = D = 23.5 ft

2.
$$N = \frac{\beta}{\sqrt{1 + \frac{\beta}{2d}} \sqrt{1 + r} \sqrt{\frac{BD^3}{\Delta L^3}}} \quad r = \frac{3.5D^2(3a^3 + 9a^2 + 6a + 1.2)}{L^2(3a + 1)}$$

$$a = \frac{B}{D}$$

3.
$$a = \frac{B}{D} = \frac{48}{23.5} = 2.04$$

$$r = \frac{3.5(23.5)^2 (3 \times 2.04^3 + 9 \times 2.04^2 + 6 \times 2.04 + 1.2)}{283^2 (3 \times 2.04 + 1)}$$

$$r = 0.259$$

4. $\beta = 97,500$

5.
$$N = \frac{97,500}{\sqrt{1 + \frac{48}{30}} \sqrt{1 + 0.259} \sqrt{\frac{48 \times 23.5^3}{2595 \times 283^3}}}$$

$$= 175.88 \text{ cpm}$$

$$N = 2.93 \text{ cps}$$

6. 2.93 cps compares favorably with 2.98 cps, the frequency of the two-noded mode computed by digital methods.

9




Figure 1 - Outboard Profile of AGS 26 Showing Station Locations




Figure 2 - Moments of Inertia Distribution for AGS 26 with respect to Horizontal Axis through Centroids of Sections




Figure 3a - 2-Noded Mode, 2.98 CPS




Figure 3b - 3-Noded Mode, 5.93 CPS




Figure 3c - 4-Noded Mode, 9.05 CPS




Figure 3d - 5-Noded Mode, 12.30 CPS




Figure 3e - 6-Noded Mode, 15.59 CPS




Figure 3f - 7-Noded Mode, 18.31 CPS

Figure 3 - Calculated Normal Mode Profiles and Natural Frequencies of Vertical Vibration




Figure 4a - 2-Noded Mode




Figure 4b - 3-Noded Mode




Figure 4c - 4-Noded Mode




Figure 4d - 5-Noded Mode




Figure 4e - 6-Noded Mode




Figure 4f - 7-Noded Mode

Figure 4 - Moment Distribution for Vertical Flexural Vibration, Assuming Unit Deflection at Stern




Figure 5 - Response to a 1-Ton Single Amplitude Sinusoidal Forcing Function at Selected Hull Stations, Damping Constant = $0.01\mu\omega$




Figure 6 - Response to a 1-Ton Single Amplitude Sinusoidal Forcing Function at Selected Hull Stations, Damping Constant = $0.03\mu\omega$

REFERENCES

1. Bureau of Ships ltr 345-175 Enclosure (1) of 14 June 1962 to David Taylor Model Basin.
2. M. Rosenblatt & Son, Inc., "Survey Ships AGS SCB Project No. 226 Contract Design Report No. CD 1180-83 Hull Vibration Study."
3. Leibowitz, R. C. and Kennard, E. H., "Theory of Freely Vibrating Nonuniform Beams, Including Methods of Solution and Application to Ships," David Taylor Model Basin Report 1317 (May 1961).
4. Gesswein, B. H. and Moses, F., "Calculated Modes and Frequencies of Hull Vibration of USS GEORGE WASHINGTON (SSBN 598) ," David Taylor Model Basin Report 1464 (Nov 1960).
5. McGoldrick, R. T., "Ship Vibration," David Taylor Model Basin Report 1451 (Dec 1960).
6. Leibowitz, R. C., "Effects of Damping on Modes of Vertical Vibration of Hull of USS THRESHER (SSN 593)," David Taylor Model Basin Report 1384 (Mar 1960).
7. Fontaine, W. R., "Calculated Natural Frequencies, Normal Modes, and Longitudinal Responses of the MST-12 Counter-Rotating Propulsion System and Coupled Hull of USS JACK (SSN 605)," David Taylor Model Basin Report 1655 (Oct 1962).
8. Todd, F. H. "Ship Hull Vibration," Edward Arnold (Publisher) Ltd. London (1961).
9. Bureau of Ships Plans, "General Arrangement, Inboard and Outboard Profiles," No. 800/2068424.
10. Bureau of Ships Plans, "Lines and Molded Offsets," No. 800/2068423.

INITIAL DISTRIBUTION

Copies

- 11 CHBUSHIPS
 - 3 Tech Lib (Code 210L)
 - 2 Ship Sil Br (Code 345)
 - 1 Lab Mgmt (Code 320)
 - 1 Mach, Sci, & Res Sec (436)
 - 1 Sci & Res Sec (442)
 - 3 Auxiliaries Br (527)
- 10 ASTIA

David Taylor Model Basin. Report 1704.

CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND NORMAL MODES OF SURVEYING SHIP AGS 26, by John T. Cummings. Mar 1963. iii, 15pp., illus., graphs, tables, refs. UNCLASSIFIED

The normal mode shapes, natural frequencies and bending moment distribution of flexural vibration of the hull were calculated for the AGS 26, a Surveying Ship. Parameters used in calculations with a digital computer are tabulated. The two-noded vertical natural frequency obtained with the computer agrees closely with that calculated using the Burrill empirical formula.

1. Surveying ships--Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 11 01

David Taylor Model Basin. Report 1704.

CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND NORMAL MODES OF SURVEYING SHIP AGS 26, by John T. Cummings. Mar 1963. iii, 15pp., illus., graphs, tables, refs. UNCLASSIFIED

The normal mode shapes, natural frequencies and bending moment distribution of flexural vibration of the hull were calculated for the AGS 26, a Surveying Ship. Parameters used in calculations with a digital computer are tabulated. The two-noded vertical natural frequency obtained with the computer agrees closely with that calculated using the Burrill empirical formula.

1. Surveying ships--Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 11 01

David Taylor Model Basin. Report 1704.

CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND NORMAL MODES OF SURVEYING SHIP AGS 26, by John T. Cummings. Mar 1963. iii, 15pp., illus., graphs, tables, refs. UNCLASSIFIED

The normal mode shapes, natural frequencies and bending moment distribution of flexural vibration of the hull were calculated for the AGS 26, a Surveying Ship. Parameters used in calculations with a digital computer are tabulated. The two-noded vertical natural frequency obtained with the computer agrees closely with that calculated using the Burrill empirical formula.

1. Surveying ships--Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 11 01

David Taylor Model Basin. Report 1704.

CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND NORMAL MODES OF SURVEYING SHIP AGS 26, by John T. Cummings. Mar 1963. iii, 15pp., illus., graphs, tables, refs. UNCLASSIFIED

The normal mode shapes, natural frequencies and bending moment distribution of flexural vibration of the hull were calculated for the AGS 26, a Surveying Ship. Parameters used in calculations with a digital computer are tabulated. The two-noded vertical natural frequency obtained with the computer agrees closely with that calculated using the Burrill empirical formula.

1. Surveying ships--Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 11 01

David Taylor Model Basin. Report 1704.
CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26, by John T.
Cummings. Mar 1963. iii, 15pp., illus., graphs,
tables, refs.
UNCLASSIFIED

The normal mode shapes, natural frequencies and
bending moment distribution of flexural vibration of
the hull were calculated for the AGS 26, a Surveying
Ship. Parameters used in calculations with a digital
computer are tabulated. The two-noded vertical
natural frequency obtained with the computer agrees
closely with that calculated using the Burrill
empirical formula.

1. Surveying ships--
Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 II 01

David Taylor Model Basin. Report 1704.
CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26, by John T.
Cummings. Mar 1963. iii, 15pp., illus., graphs,
tables, refs.
UNCLASSIFIED

The normal mode shapes, natural frequencies and
bending moment distribution of flexural vibration of
the hull were calculated for the AGS 26, a Surveying
Ship. Parameters used in calculations with a digital
computer are tabulated. The two-noded vertical
natural frequency obtained with the computer agrees
closely with that calculated using the Burrill
empirical formula.

1. Surveying ships--
Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 II 01

David Taylor Model Basin. Report 1704.
CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26, by John T.
Cummings. Mar 1963. iii, 15pp., illus., graphs,
tables, refs.
UNCLASSIFIED

The normal mode shapes, natural frequencies and
bending moment distribution of flexural vibration of
the hull were calculated for the AGS 26, a Surveying
Ship. Parameters used in calculations with a digital
computer are tabulated. The two-noded vertical
natural frequency obtained with the computer agrees
closely with that calculated using the Burrill
empirical formula.

1. Surveying ships--
Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 II 01

David Taylor Model Basin. Report 1704.
CALCULATED NATURAL VERTICAL HULL FREQUENCIES AND
NORMAL MODES OF SURVEYING SHIP AGS 26, by John T.
Cummings. Mar 1963. iii, 15pp., illus., graphs,
tables, refs.
UNCLASSIFIED

The normal mode shapes, natural frequencies and
bending moment distribution of flexural vibration of
the hull were calculated for the AGS 26, a Surveying
Ship. Parameters used in calculations with a digital
computer are tabulated. The two-noded vertical
natural frequency obtained with the computer agrees
closely with that calculated using the Burrill
empirical formula.

1. Surveying ships--
Vibration--Mathematical analysis
 2. Ship hulls--vibration
 3. Digital computers--Applications
 4. AGS 26 (U.S. surveying ships)
- I. Cummings, John T.
II. S-F013 II 01

MIT LIBRARIES

DUPL



3 9080 02754 4458

